



## UNIVERSAL ECO ULTRA SYNTHETIC BLEND ENGINE OILS

Universal ECO ULTRA Synthetic Blend Engine Oils are blended with highly re-refined Group II base oils and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. Universal ECO ULTRA Synthetic Blend Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

PROPERTY	ASTM TEST METHOD	SAE 5W20	SAE 5W30	SAE 10W30
Viscosity @ -30°C, cP	D5293	5000	6100	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	5700
Viscosity @ 40°C, cSt	D445	46.00	64.00	68.00
Viscosity @ 100°C, cSt	D445	8.20	10.60	10.40
Viscosity Index	D2270	152	157	140
Flash Point, COC, °C	D92	229	231	231
Flash Point, COC, °F	D92	421	448	448
Pour Point, °C	D97	-40	-40	-36
Pour Point, °F	D97	-40	-40	-33
Color	D1500	3.0	3.0	2.5
Gravity, NAPI	D4052	32.8	32.6	29.5
HT/HS, cP	D4683	2.6	3.1	3.0

### Meets or exceeds the following tests and requirements:

API Service Classification - SN, ILSAC GF-5

Chrysler MS-11999, MS-12007, MS-12015

Resource Conserving

Ford Motor Company - WSS-92C945-A, WSS-92C946-A

Honda

Toyota

NOTE: Certain tests apply to specific SAE grades.