



Fleet Supreme EC[®] Engine Oil

Fleet Fleet Supreme EC (Emission Compatible) is an API CJ-4 engine oil developed for use in four-stroke cycle diesel engines designed to meet 2007 and later EPA on-highway exhaust emissions standards. It is specially formulated to protect exhaust aftertreatment devices such as diesel particulate filters (DPFs), diesel oxidation catalysts (DOCs) and selective catalytic reduction (SCR) systems. It is backward serviceable for use in pre-2007 diesel engines, and may be used in mixed fleets with both diesel and gasoline-fueled vehicles.

Fleet Supreme EC is designed for use in mixed fleets with both on-highway and off-road equipment operating in varying climates and under varying loads and service conditions. It has excellent soot dispersancy to protect against soot-induced oil thickening and abrasive wear, and excellent oxidation resistance to help minimize deposit formation. The low-ash formulation is designed for compatibility with all exhaust emission control systems in modern diesel engines, and to help prolong DPF life.

Fleet Supreme EC meets or exceeds the performance requirements of API Service Categories CJ-4 and SN, and is approved under the latest OEM specifications for use in low-emission diesel engines. It is formulated for use in diesel engines operating on diesel fuels with sulfur content up to 500 ppm. However, for use with non-ULSD (Ultra-Low Sulfur Diesel) fuels with sulfur content greater than 15 ppm, consult the engine manufacturer for recommended service interval.

Applications

- On-highway diesel trucks equipped with EGR and exhaust aftertreatment devices to meet 2007/2010 emissions standards
- Older diesel equipment with conventional, non-EGR engines or ACERT engines
- Off-highway construction, earth moving and mining equipment
- Mixed fleets with diesel and gasoline-fueled vehicles

Fleet Supreme EC meets or exceeds the requirements of:

- API Service CJ-4, CI-4 with CI-4 PLUS, CI-4, CH-4, SN
- ACEA E9-08, E7-04 (SAE 15W-40)
- Caterpillar ECF-3, ECF-2, ECF-1-a

**API CJ-4 Diesel
Engine Oil For
Low-Emission
Engines**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-877-445-9198**

**International
Customer Service:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**



- Chrysler MS-10902 (SAE 15W-40)
- Cummins CES 20081
- Detroit Diesel Power Guard 93K218 (SAE 15W-40), Power Guard 93K214 (SAE 15W-40), 7SE270 (4-stroke cycle engines)
- Ford WSS-M2C171-E
- International (Navistar) diesel engines
- Mack EO-O Premium Plus (SAE 15W-40), EO-M Plus (both grades)
- Mercedes-Benz Sheet 228.31 (SAE 15W-40)
- MTU MTL 5044 Type 2.1 (SAE 15W-40)
- Volvo VDS-4, VDS-3, VDS-2 (SAE 15W-40)
- Diesel engines manufactured by OEMs not listed above, where the OEM specifies API CJ-4 engine oil

Features/Benefits

- Excellent protection for newer low-emission diesel engines and older diesel engines
- Specially formulated to protect exhaust aftertreatment devices
- Protects against particulate filter plugging
- Excellent soot control for protection against abrasive wear and soot-induced oil thickening
- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust, bearing corrosion and wear
- Good resistance to foaming and aeration

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2012 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.



Fleet Supreme EC[®] Engine Oil

Typical Properties

SAE Grade	10W-30	15W-40
Specific Gravity @ 60°F	0.872	0.880
Density, lbs/gal @ 60°F	7.26	7.33
Color, ASTM D1500	4.0	4.0
Flash Point (COC), °C (°F)	227 (441)	227 (441)
Pour Point, °C (°F)	-45 (-49)	-38 (-36)
Viscosity, Kinematic		
cSt @ 40°C	80.0	114
cSt @ 100°C	12.0	15.2
Viscosity Index	146	137
Cold Cranking Viscosity, cP	6,200	6,500
@ (°C)	(-25)	(-20)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.6	4.3
Sulfated Ash, ASTM D874, wt %	0.97	0.97
Total Base Number (TBN), ASTM D2896	8.4	8.4
Zinc, wt %	0.121	0.121

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2012 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.