



GT-1® High Performance Motor Oil, Nitro 70

Kendall® GT-1 High Performance Motor Oil, Nitro 70, is a high-quality engine oil specially formulated for use in nitromethane- and alcohol-fueled drag racing vehicles. It is not recommended for use in passenger cars or light trucks.

GT-1 High Performance Motor Oil, Nitro 70, is formulated to provide excellent wear protection and resistance to viscosity and thermal breakdown at high temperatures. It has excellent oxidation resistance and a high level of detergency to help minimize deposit formation. Its high viscosity helps maintain a protective oil film in the presence of fuel dilution.

Applications

- Nitromethane- and alcohol-fueled competition engines

Features/Benefits

- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Excellent wear protection
- High viscosity to help counteract fuel dilution
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Highly resistant to foaming
- Racetrack-proven performance

**Engine Oil For
Nitromethane- and
Alcohol-Fueled
Competition
Engines**

U.S. Customer
Service:

1-800-368-7128

Technical Hot Line:

1-877-445-9198

International
Customer Service:

1-832-486-3363

E-mail address:

**kendallmotoroil@
conocophillips.com**

GT-1® High Performance Motor Oil, Nitro 70**Typical Properties**

Grade	Nitro 70
Specific Gravity @ 60°F	0.902
Density, lbs/gal @ 60°F	7.51
Color, ASTM D1500	5.0
Flash Point (COC), °C (°F)	230 (446)
Pour Point, °C (°F)	-9 (16)
Viscosity, Kinematic	
cSt @ 40°C	420
cSt @ 100°C	30
Viscosity Index	101
High-Temp/High-Shear Viscosity, cP @ 150°C	>5.0
Sulfated Ash, ASTM D874, wt %	1.6
Total Base Number (TBN), ASTM D2896	12
Phosphorus, wt %	0.233
Zinc, wt %	0.257

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2011 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.