



GT-1® High Performance Synthetic Blend Motor Oil with Liquid Titanium®

Kendall® GT-1 High Performance Synthetic Blend Motor Oil with Liquid Titanium protection additive is a premium quality, part-synthetic engine oil designed for use in gasoline-fueled and flex-fuel passenger cars and light trucks under all operating conditions.

GT-1 High Performance Synthetic Blend with Liquid Titanium is formulated with a blend of synthetic and conventional base stocks and a performance additive package fortified with our exclusive Liquid Titanium protection additive for extra protection against engine wear and improved fuel savings. The part-synthetic formulation provides enhanced oxidation resistance and thermal stability at high temperatures and better pumpability at low temperatures compared with conventional engine oils, for extra protection under all driving conditions. Our Liquid Titanium protection additive provides increased engine protection by forming a strongly bonded titanium shield on the surface of critical engine parts, which reduces friction and wear and helps extend engine life. Reduced friction also helps improve fuel economy performance beyond ILSAC GF-5 requirements.

GT-1 High Performance Synthetic Blend with Liquid Titanium exceeds new car warranty requirements as defined by ILSAC GF-5. It is "Resource Conserving" for improved fuel economy, protection of emissions system catalysts and turbochargers, and protection of engines operating on ethanol-containing fuels up to E85.

Applications

- Gasoline-fueled and flex-fuel passenger cars, light trucks and sport utility vehicles

GT-1 High Performance Synthetic Blend with Liquid Titanium meets or exceeds the requirements of:

- ILSAC GF-5
- API Service SN with Resource Conserving
- Chrysler MS-6395 (Rev. T)
- Ford WSS-M2C945-A (SAE 5W-20), WSS-M2C946-A (SAE 5W-30)
- GM6094M (obsolete)

**Premium
Synthetic Blend
Passenger Car
Engine Oil;
Fortified With
Liquid Titanium®
Protection Additive**



U.S. Customer
Service:

1-800-368-7128

Technical Hot Line:

1-877-445-9198

International
Customer Service:

1-832-486-3363

E-mail address:

**kendallmotoroil@
conocophillips.com**

www.conocophillipslubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Features/Benefits

- Exceeds ILSAC GF-5 requirements for new cars under warranty
- Part-synthetic formulation provides enhanced performance benefits compared with conventional engine oils
- Exclusive Liquid Titanium® protection additive provides extra protection against engine wear and improved fuel economy
- Excellent resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Low volatility for reduced oil consumption
- Excellent low-temperature pumpability for protection during cold starts
- Highly resistant to foaming
- Formulated to protect turbochargers and emissions control system catalysts
- Formulated for use in vehicles operating on ethanol-containing fuels up to E85

GT-1® High Performance Synthetic Blend Motor Oil with Liquid Titanium®

Typical Properties

SAE Grade	5W-20	5W-30	10W-30
Specific Gravity @ 60°F	0.860	0.861	0.870
Density, lbs/gal @ 60°F	7.16	7.17	7.24
Color, ASTM D1500	3.5	3.0	3.5
Flash Point (COC), °C (°F)	218 (424)	216 (421)	229 (444)
Pour Point, °C (°F)	<-42 (<-44)	<-42 (<-44)	<-42 (<-44)
Viscosity, Kinematic			
cSt @ 40°C	47.0	67.0	68.0
cSt @ 100°C	8.7	10.8	10.4
Viscosity Index	151	162	152
Cold Cranking Viscosity, cP	5,400	5,900	4,500
@ (°C)	(-30)	(-30)	(-25)
High-Temp/High-Shear Viscosity, cP @ 150°C	2.6	3.2	3.2
Sulfated Ash, ASTM D874, wt %	1.0	1.0	1.0
Total Base Number (TBN), ASTM D2896	8.6	8.6	8.6
Phosphorus, wt %	0.077	0.077	0.077
Titanium, wt %	0.010	0.010	0.010
Zinc, wt %	0.085	0.085	0.085

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2011 ConocoPhillips Company. ConocoPhillips, Kendall, their respective logos, the Two Finger logo, and Liquid Titanium are trademarks of the ConocoPhillips Company in the U.S.A. and other countries.